

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 September 2001 (07.09.2001)


PCT

(10) International Publication Number
WO 01/64529 A2

- (51) International Patent Classification⁷: **B65D 5/00**
- (21) International Application Number: PCT/US01/06103
- (22) International Filing Date: 27 February 2001 (27.02.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/185,706 29 February 2000 (29.02.2000) US
- (71) Applicant: **TRI STATE DISTRIBUTION, INC.**
[US/US]; HC 69, Box 398, Spencer, TN 38585 (US).
- (72) Inventors: **MICELI, David, A.**; c/o Tri State Distribution, Inc., HC 69, Box 398, Spencer, TN 38585 (US). **MICELI, Joseph, A.**; c/o Tri State Distribution, Inc., HC 69, Box 398, Spencer, TN 38585 (US).
- (74) Agents: **WOODWARD, David, W.** et al.; Shanks & Herbert, TransPotomac Plaza, Suite 306, 1033 North Fairfax Street, Alexandria, VA 22314 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: REVERSIBLE CHILD RESISTANT CAP AND COMBINATION OF A CONTAINER AND A REVERSIBLE CHILD RESISTANT CAP



(57) Abstract: The present invention relates to a reversible child resistant cap and a closure system having two positions, the first being a child resistant position and the other being a non-child resistant position. The cap is characterized in that it has a closure plane, a circumferential outer skirt for engaging a container, and a circumferential resilient depending inner member.

WO 01/64529 A2



IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*

Reversible Child Resistant Cap and Combination of a Container and a Reversible Child Resistant Cap

TECHNICAL FIELD AND INDUSTRIAL APPLICABILITY

The present invention relates to a reversible child resistant cap.

- 5 Specifically, the invention relates to a cap which may be applied to a vial or other container in one of two positions, the first being a child resistant position and the second being a non-child resistant position. The child resistant position provides an obstacle to children being able to remove the cap from the container, whilst the non-child resistant position allows for ready removal of the
- 10 cap from the container. The present invention also provides a reversible child resistant cap and container assembly.

BACKGROUND OF THE INVENTION

- There are many varying types of child resistant closure systems disclosed in the art. An example of a particular type of child resistant closure
- 15 system is disclosed in U.S. Patent No. 5,449,078, which relates to a combination of a container and safety cap. The aforementioned patent is herein incorporated by reference.

- While many child resistant caps effectively provide protection against the danger of small children being able to remove potentially harmful pills from
- 20 vials or other containers, they also provide a problem for a considerable portion of the adult population that require medication, however, lack the manual dexterity or strength to remove the child resistant cap. This is of a particular concern to the elderly population or people suffering from arthritis and other debilitating diseases.

- 25 Accordingly, this problem has been addressed by the development of closure systems having a child resistant mode and a non-child resistant mode such that, in the non-child resistant mode, the caps are more easily opened by adults. However, many such caps have a complex, multi part, structure making the caps expensive or the closure systems suffer from the problem of

providing an inferior moisture and air barrier when used in the non-child resistant mode. Further, other attempts to develop reversible child resistant closure systems have resulted in caps that when used in their non-child resistant mode tended to come off from the vial or container inadvertently, for example, when being carried in a bag with other articles.

In light of the foregoing, there is a need for a reversible child resistant closure that overcomes the aforementioned deficiencies of the prior art.

SUMMARY OF THE INVENTION

10

Accordingly, the present invention is directed to a reversible child resistant cap and closure system that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

Additional features and advantages of the invention will be set forth in the description that follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the system particularly pointed out in the written description and claims hereof as well as the appended drawings.

20 To achieve these and other advantages and in accordance with the purpose of the invention, as embodied and broadly described, the invention provides a reversible child resistant cap. In the first position, or child resistant position, the cap when applied to a container provides an effective protection against children being able to remove the closure, whilst at the same time
25 allow ready removal of the cap by normal adults. In the second position, or the non-child resistant position, the cap allows for easy removal of the cap from the container even by persons whose ability to use their hands is severely limited.

In another embodiment, the present invention also provides a reversible
30 child resistant closure system, comprising the combination of a container and reversible child resistant cap.

In accordance with the invention, the reversible child resistant cap comprises a closure plane, a circumferential outer skirt for engaging a container, and a circumferential resilient depending inner member. The circumferential outer skirt comprises an upper portion extending in an upward direction from the closure plane and a lower portion extending in a downward direction from the closure plane. The upper portion of the circumferential outer skirt comprises a non-child resistant engaging means for engaging a container. The lower portion of the circumferential outer skirt comprises a child resistant engaging means for engaging a container. The circumferential resilient depending inner member has an outer surface that is tapered from a larger diameter portion adjacent the closure plane to a smaller diameter portion remote from the closure plane.

In accordance with another embodiment of the invention, the reversible child resistant closure system comprises a cap and a container. The cap comprises a closure plane and a circumferential outer skirt for engaging the container and having a circumferential resilient depending inner member. The circumferential outer skirt comprises an upper portion extending in an upward direction from the closure plane and a lower portion extending in a downward direction from the closure plane. The upper portion of the circumferential outer skirt comprises a non-child resistant engaging means for engaging the container. The lower portion of the circumferential outer skirt comprises a child resistant engaging means for engaging the container. The circumferential resilient depending inner member has a tapered outer surface that is tapered from a larger diameter portion adjacent the closure plane to a smaller diameter portion remote from the closure plane. The container has a rigid wall having an engaging end for engagement with the cap. The engaging end of the container has an outer surface for engaging the non-child resistant engaging means of the cap. The engaging end of the container also has an inner surface for engaging the tapered outer surface of the cap to provide a seal and a bias on the cap in a direction of removal of the cap. The container also includes means disposed on the container remotely from the engaging end of the

container in cooperative means with the child resistant engaging means of the cap.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are
5 intended to provide further explanation of the invention as claimed.

The accompanying drawings are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate several embodiments of the invention and together with the description serve to explain the principles of the invention.

10 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an embodiment of the reversible child resistant cap and container assembly in its first child resistant position.

FIG. 2 is a perspective view of the cap of FIG. 1 in its first child resistant position.

15 FIG. 3 is a perspective view of the cap of FIG. 1 in its second non-child resistant position.

FIG. 4 is a top view of the cap of FIG. 1 in its first child resistant position.

FIG. 5 is a bottom view of the cap of FIG. 1 in its first child resistant position.

FIG. 6 is a cross sectional view of the cap of FIG. 4 as viewed along line A-A.

20 FIG. 7 is a cross sectional view of the cap of FIG. 4 as viewed along line B-B.

FIG. 8 is a cross sectional view of the cap of FIG. 4 as viewed along line C-C.

FIG. 9 is a more detailed view of FIG. 6.

FIG. 10 is a top view of a first embodiment of the container of the present invention.

25 FIG. 11 is a side view of the first embodiment of the container of the present invention.

FIG. 12 is a bottom view of the first embodiment of the container of the present invention.

FIG. 13 is a cross sectional view of the container depicted in FIG. 10 as
30 viewed along line E-E.

FIG. 14 is a fragmentary elevational view, partly in sectional, of the container and the neck thereof with the cap thereon in a locked and sealed position.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS OF THE
PRESENT INVENTION

Referring now to the drawings of the present disclosure in which like numbers represent the same structure in the various views, a perspective view of an embodiment of the reversible child resistant closure system of the present invention is shown generally at 1 in FIG. 1 and comprises a reversible child resistant cap 2 and a container 3. Specifically, FIG. 1 shows the reversible child resistant closure system in the first child resistant position. Thus, when the closure system is in the first child resistant position the child resistant engaging means of the cap mates with the child resistant engaging means on the container. However, the cap 2 may also be used in an inverted orientation, as shown in FIG. 3, i.e. in a second non-child resistant position. In this second non-child resistant position the non-child resistant engaging means of the cap engage with the non-child resistant engaging means of the container.

FIGS. 6, 7 and 8 are cross sectional views of a preferred embodiment of the cap 2 depicted in FIG 4. taken along lines A-A, B-B, and C-C respectively. A more detailed view of FIG. 6 is provided by FIG. 9. As shown in FIGS. 4-9, the reversible child resistant cap 2 a closure plane 5, a circumferential outer skirt 10, and a circumferential resilient depending inner member 15.

The circumferential outer skirt 10 comprises an upper portion 20 extending in an upward direction from the closure plane 5. The outer skirt 10 also comprises a lower portion 25 extending in a downward direction from the closure plane 5. The upper portion 20 of the circumferential outer skirt comprises a non-child resistant engaging means for engaging the container. Any suitable non-child resistant engaging means may be used. Suitable examples include an endless closure bead, a thread bead, and a double thread bead. FIGS. 4-9 depict a thread bead 30 as the non-child resistant engaging means, however, a double entry thread bead is preferred. The lower

portion **25** of the circumferential outer skirt **10** comprises a child resistant engaging means for engaging the container **3**. Any suitable child resistant engaging means may be used. In the preferred embodiment shown in FIGS. 2-9 the suitable child resistant engaging means comprises one or more locking
5 lugs **35**.

The circumferential outer skirt **10** may also comprise a gripping means to facilitate rotation of the cap **2** to aid in both putting the cap onto the container and then the subsequent removal of the cap **2**. Any suitable gripping means may be utilized. In a preferred embodiment, knerlments **37** are
10 disposed about the outer surface of the outer skirt **10**.

The circumferential resilient depending inner member **15** has an outer surface **40** which is tapered from a larger diameter portion adjacent the closure plane **5** to a smaller diameter portion remote from the closure plane **5**.

Referring to FIGS. 11-13, the container **3** has a neck portion **45** having
15 an inner surface **50** for engaging the tapered outer surface **40** of the cap **2**. When the closure system of the present invention is used in the first child resistant position, the inner surface **50** engages the tapered outer surface **40** of the cap to provide a seal. Further, the neck portion **45** is preferably made such that when the inner surface **50** engages the outer surface **40**, the neck
20 portion **45** bends or flexes in an outward direction to provide a bias on the cap **2** in a direction of removal of the cap **2**. The neck **45** may have any suitable construction to provide the bias on the cap **2**. For example, the neck **45** may have a thickness sufficiently thin such that the neck **45** flexes or bends in an outward direction when the cap **2** is locked in the first child resistant position.
25 The neck **45** of the container **3** also comprises a top edge surface **55** which contacts the closure plane **5** of the cap **2** when the closure system is in the second non-child resistant position. This contact of the top edge surface **55** and the closure plane **5** is sufficient to form a seal. A non-child resistant engaging means is disposed about the outer surface **60** of the neck **45** to
30 engage the non-child resistant engaging means of the cap **2**. Any suitable engaging means may be used. Suitable engaging means may include an endless bead, a thread bead, and a double entry thread bead. As shown in

FIGS. 10 and 11, in a preferred embodiment a double entry thread bead 65 is used.

The container 3 also comprises a child resistant engaging means disposed on the container remotely from the neck 45 to cooperate with the child resistant engaging means of the cap 2. In a preferred embodiment, the child resistant engaging means disposed on the container cooperates with the child resistant engaging means on the cap 2 to prevent the cap 2 from being removed from the container without the simultaneous depression and rotation of the cap 2 on the container 3. Referring now to FIG. 11 the child resistant engaging means on the container 3 comprises a camming latch 70 having a cam receiving notch 75 therein and in which the child resistant engaging means on the cap 2 comprises a locking lug 35 which is guided into the notch 75 upon rotation of the cap 2 on the container 3 when the cap 2 is applied to close and seal the container 3 in the first child resistant position.

FIG. 14 represents the cap 2 on the container 3 in its first child resistant position with the locking lug 35 seated in notch 75 so that the cap 2 is locked on the container 3. The tapered outer surface 40 of the cap is disposed inside the inner surface 50 of the neck 45 of the container 3 causing an upward bias on the cap 2. Accordingly, the cap cannot be removed from the container merely by rotating the cap 2. Instead, the cap 2 must be depressed on the container to unseat the lock lug 35 from the notch 75 and then rotated in a counter clockwise direction so that the lock lug can be positioned between camming latch 70 and the next adjacent camming latch, so that the cap 2 can be removed by then directly upward motion.

In a particularly preferred embodiment, the cap 2 and the container 3 of the present invention have the following dimensions $7/1$, $7/2$, $8/1$, $8/2$, $8/3$, $8/4$, $8/5$, $8/6$, $9/1$, $9/2$, $9/3$, $9/4$, $9/5$, $9/6$, $9/7$, $9/8$, $9/10$, $11/1$, $11/2$, $11/3$, $13/1$, and $13/2$ as depicted in FIGS. 7, 8, 9, 11 and 13. In a more preferred embodiment angle α as depicted in FIG. 6 is about 3 degrees. In an even more preferred embodiment, some or all dimensions $7/1$, $7/2$, $8/1$, $8/2$, $8/3$, $8/4$, $8/5$, $8/6$, $9/1$, $9/2$, $9/3$, $9/4$, $9/5$, $9/6$, $9/7$, $9/8$, $9/10$, $11/1$, $11/2$, $11/3$, $13/1$, and $13/2$ are 0.125, 1.184,

1.313, 1.254, 1.010, 1.160, 1.314, 1.204, 1.020, 0.950, 0.040, 0.230, 0.615, 0.075, 0.230, 0.345, 0.150, 1.076, 0.090, 1.190, and 1.190 mm respectively.

Any suitable method known to one of ordinary skill in the art may be used to manufacture the cap 2 and container 3 of the present invention.

- 5 However, to aid in the manufacture of the cap 2 of the present invention, comprising a locking lug 35, the cap 2 preferably comprises molding holes 90 positioned above each locking lug 35 such that portions of an upper mold may pass through the molding holes to form the top surface 80 of the locking lug 35. To retain the moisture and air barrier properties of the closure system, the
- 10 molding holes 90 are positioned between the outer surface of the skirt 10 and the position at which the closure plane 5 contacts the top edge surface 55 of the container 3 when the cap 2 is applied to the container 3 in the second non-child resistant position. The use of molding holes 90 also enables the locking lug 35 to protrude a greater amount from the inner surface 85 of the lower
- 15 portion 25 of the skirt 10 than would otherwise be achievable. In addition, the molding holes also allows the locking lug 35 to have a top surface 80 that is substantially perpendicular to the inner surface 85 of the lower portion 25 of the outer skirt 10.

Preferably, the cap is linerless, but liners may be provided if desired.

- 20 The cap is preferably made from a plastic material, such as high density polyethylene (HDPE) or polypropylene. The container is preferably made from a plastic material, such as low density polyethylene (LDPE) or polypropylene. More preferably, the container is made from polypropylene. The skilled artisan, having the benefit of the instant disclosure, will readily appreciate that
- 25 the caps and containers may be made from other suitable materials.

- Numerous alterations of the structure herein disclosed will be apparent to one of ordinary skill in the art. However, it is understood that the present disclosure relates to preferred embodiments of the invention for the purposes of illustration only and should not be construed as to be a limitation of the
- 30 invention. All such modifications and alterations which do not depart from the spirit of the invention are intended to be included within the appended claims.

WHAT IS CLAIMED IS:

1. A reversible child resistant cap for use with a container, the cap having a child resistant mode when applied to the container in a first child resistant position and having a non-child resistant mode when applied to the container
5 in a second non-child resistant position, the cap comprising:
a closure plane;
a circumferential outer skirt comprising an upper portion extending in an upward direction from the closure plane and a lower portion extending in a downward direction from the closure plane, wherein the upper portion of the
10 circumferential outer skirt comprises a non-child resistant engaging means for engaging the container and the lower portion of the circumferential outer skirt comprises a child resistant engaging means for engaging the container; and
a circumferential resilient depending inner member comprising an outer surface, wherein the outer surface is tapered from a larger diameter portion
15 adjacent the closure plane to a smaller diameter portion remote from the closure plane.
2. The reversible child resistant cap according to claim 1, wherein the circumferential outer skirt further comprises a gripping means.
3. The reversible child resistant cap according to claim 2, wherein the
20 gripping means comprises a plurality of knurlments.
4. The reversible child resistant cap according to claim 1, wherein the non-child resistant engaging means is an endless closure bead.
5. The reversible child resistant cap according to claim 1, wherein the non-child resistant engaging means is a thread bead.
- 25 6. The reversible child resistant cap according to claim 1, wherein the non-child resistant engaging means is a double entry thread bead.
7. The reversible child resistant cap according to claim 1, wherein the non-child resistant engaging means extends from an inner surface of the upper portion of the circumferential outer skirt.
- 30 8. The reversible child resistant cap according to claim 1, wherein the child resistant engaging means is a locking lug.

9. The reversible child resistant cap according to claim 8, wherein the cap further comprises a molding hole positioned above the locking lug between an outer surface of the circumferential outer skirt and a position on the closure plane at which position the closure plane intersects with a top edge surface of the container when the cap is applied to the container in the second non-child resistant position.

10. The reversible child resistant cap according to claim 1, wherein the locking lug has a top surface plane about perpendicular to an inner surface of the lower portion of the circumferential outer skirt.

10 11. The reversible child resistant cap according to claim 1, wherein the cap is molded from polypropylene.

12. A closure system comprising a reversible child resistant cap and a container, having a child resistant mode when the cap is applied to the container in a first child resistant position and having a non-child resistant mode when the cap is applied to the container in a second non-child resistant position;

wherein the cap comprises:

(i) a closure plane;

(ii) a circumferential outer skirt comprising an upper portion extending in an upward direction from the closure plane and a lower portion extending in a downward direction from the closure plane, wherein the upper portion of the circumferential outer skirt comprises a non-child resistant engaging means for engaging the container and the lower portion of the circumferential outer skirt comprises a child resistant engaging means for engaging the container; and

(iii) a circumferential resilient depending inner member comprising an outer surface, wherein the outer surface is tapered from a larger diameter portion adjacent the closure plane to a smaller diameter portion remote from the closure plane; and

30 the container comprises:

(i) a neck portion, wherein the neck portion of the container has an inner surface for engaging the tapered outer surface of the cap to provide a

seal and a bias on the cap in a direction of removal of the cap when the closure system is used in the first child resistant position; a top edge surface for engaging the closure plane of the cap to provide a seal when the closure system is used in the second non-child resistant mode; and a non-child resistant engaging means disposed on an outer surface of the neck portion for engaging the cap when the closure system is used in the second non-child resistant position; and
(ii) a child resistant engaging means disposed on the container remotely from said neck portion.

10 13. The closure system according to claim 12, wherein the non-child resistant engaging means of the cap is an endless closure bead and the non-child resistant engaging means of the container is an endless closure bead positioned to engage the endless closure bead of the cap when the closure system is used in the second non-child resistant position.

15 14. The closure system according to claim 12, wherein the non-child resistant engaging means of the cap is a thread bead and the non-child resistant engaging means of the container is a thread bead positioned to engage the thread bead of the cap when the closure system is used in the second non-child resistant position.

20 15. The closure system according to claim 12, wherein the non-child resistant engaging means of the cap is a double entry thread bead and the non-child resistant engaging means of the container is a double entry thread bead positioned to engage the double entry thread bead of the cap when the closure system is used in the second non-child resistant position.

25 16. The closure system according to claim 12, wherein the child resistant engaging means of the cap and the child resistant engaging means of the container engage to prevent the cap from being removed from the container without depression of the cap and rotation of the cap on the container, when the closure system is in its first child resistant position.

30 17. The closure system according to claim 16, wherein the child resistant engaging means of the container comprises a camming latch having a cam-receiving notch therein and in which the child resistant engaging means of the

cap comprises a locking lug which is guided into the notch upon rotation of the cap on the container when the cap is applied to close and seal the container in the first child resistant position.

18. The closure system according to claim 17, wherein the cap further
5 comprises a molding hole positioned above the locking lug between an outer surface of the circumferential outer skirt and a position on the closure plane at which position the closure plane intersects with the top edge surface of the container when the cap is applied to the container in the second non-child resistant position.
- 10 19. The closure system according to claim 17, wherein the locking lug has a top surface plane about perpendicular to an inner surface of the lower portion of the circumferential outer skirt.
20. The closure system according to claim 12, wherein the container is molded from polypropylene.
- 15 21. The closure system according to claim 12, wherein the container is selected from the group consisting of a vial and a bottle.

1/10






FIG.1

2/10



3/10




FIG. 4





FIG. 5

4/10



5/10




FIG. 7




FIG. 8

6/10






FIG.9



8/10




FIG. 12

9/10




FIG. 13

10/10




FIG. 14

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 September 2001 (07.09.2001)

PCT


(10) International Publication Number
WO 01/64529 A3

- (51) International Patent Classification⁷: **B65D 50/00**,
41/06, 50/04
- (21) International Application Number: PCT/US01/06103
- (22) International Filing Date: 27 February 2001 (27.02.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/185,706 29 February 2000 (29.02.2000) US
- (71) Applicant: **TRI STATE DISTRIBUTION, INC.**
[US/US]: HC 69, Box 398, Spencer, TN 38585 (US).
- (72) Inventors: **MICELI, David, A.**; c/o Tri State Distribution,
Inc., HC 69, Box 398, Spencer, TN 38585 (US). **MICELI,**
- (54) Title: CONTAINER WITH A REVERSIBLE CHILD RESISTANT CAP
- (74) Agents: **WOODWARD, David, W.** et al.: Shanks & Herbert, TransPotomac Plaza, Suite 306, 1033 North Fairfax Street, Alexandria, VA 22314 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]



WO 01/64529 A3



(57) Abstract: The present invention relates to a reversible child resistant cap (2) and a closure system having two positions, the first being a child resistant position and the other being a non-child resistant position. The cap (2) is characterized in that it has a closure plane (5), a circumferential outer skirt (10) for engaging a container (3), and a circumferential resilient depending inner member (15).



IT, LU, MC, NL, PT, SE, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:
21 February 2002

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/06103

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B65D50/00 B65D41/06 B65D50/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 452 364 A (KAY RONALD D) 5 June 1984 (1984-06-05) column 1-3; figures 1-4 ---	1-3, 7-10,12, 16-19,21
Y	US 5 449 078 A (AKERS EDWARD G) 12 September 1995 (1995-09-12) cited in the application column 1-4; figures 1-10 ---	1-3, 7-10,12, 16-19,21
A	EP 0 792 818 A (OWENS ILLINOIS PRESCRIPTION PR) 3 September 1997 (1997-09-03) column 2, line 24-28; figures 1-7 --- -/--	1-3,5,8, 12,14, 16,17,21



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

26 September 2001

Date of mailing of the international search report

05/10/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vollering, J

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 01/06103

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 924 588 A (BRENNAN V JACK) 20 July 1999 (1999-07-20) column 6, line 37-59; figures 1-9 ---	1-3,6,8, 12, 15-17,21
A	US 3 865 267 A (MORRIS GLENN H) 11 February 1975 (1975-02-11) column 3, line 31 -column 7, line 38; figures 1-18 ---	4,13
A	US 4 526 281 A (HERR JAMES E) 2 July 1985 (1985-07-02) -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/06103

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4452364	A	05-06-1984	NONE	
US 5449078	A	12-09-1995	AU 685303 B2 AU 2950895 A CA 2194452 A1 EP 0770020 A1 WO 9601768 A1	15-01-1998 09-02-1996 25-01-1996 02-05-1997 25-01-1996
EP 0792818	A	03-09-1997	US 5711442 A AU 710407 B2 AU 1502097 A CA 2198683 A1 EP 0792818 A1	27-01-1998 16-09-1999 04-09-1997 29-08-1997 03-09-1997
US 5924588	A	20-07-1999	NONE	
US 3865267	A	11-02-1975	CA 1049447 A1 DE 2460284 A1 FR 2255227 A1 GB 1495532 A IT 1023960 B JP 50096381 A JP 56084269 A US RE29779 E	27-02-1979 03-07-1975 18-07-1975 21-12-1977 30-05-1978 31-07-1975 09-07-1981 26-09-1978
US 4526281	A	02-07-1985	NONE	